# **B-BLOCK GLOSSY CK**



#### **ANTI STAIN GLOSSY EFFECT**

Long lasting, durable, water based, protective shining effect for indoor and outdoor surfaces in terracotta, klinker and quarry tiles.



#### **CHEMICAL PROPERTIES**

APPEARANCE: Liquid

COLOUR: White

ODOUR: Characteristic

SOLUBILITY: Miscible in water

PH: 8,80 ± 0,50

#### **COVERAGE FOR LITRE**

Unglazed terracotta: Approximately 15-20 m<sup>2</sup>

(Product coverage may vary depending on type and porosity of material where used)

PACKAGING		
Code	Content	Pc./Carton
P115BGCK10L	1 lt	6
P115BGCK50L	5 lt	4

for information: www.bellinzoni.com

# MADE IN ITALY●○●

## **SURFACES**

The product is recommended for terracotta an, klinker, bricks and quarry tiles.

## **FEATURES**

The treated surfaces will be greatly protected against spillages of olive and seeds oils, coffee, tea, ketchup, mustard etc. The product Easy-Clean property will make the cleaning easier while giving a shinier, darker "wet look" to the material. It prevents water stagnation and moisture absorption, avoiding mildew and mould build ups.

## **HOW TO USE**

Remove all debris, dust and previous applied waxes from the surface using XTREME HD CLEANER or SUPER CLEANER. The surfaces must be dust free, clean and dry before application. The product is ready to use. Apply a thin coat of product uniformly in one direction using a brush, microfiber cloth, wax applicator or roller. Let it dry for approximately 15-20 minutes before applying a second coat in the opposite direction from the fist. Remove the excess product or residues, if any, within 15 minutes with a cotton or microfiber cloth.

## **ADVANTAGES**

Durable long-lasting protection. Its low VOC content allows the product to be used indoors. It gives the surfaces a "wet-look" shinier finish and makes the floor maintenance easier. It is a protective with low VOC content of 2,80% (directive 2010/75/UE).

## **ADVICE**

Do not walk on the treated surfaces for at least 6-8 hours from application. The surfaces are fully protected after 24 hours from application. Do not over apply. The product may have difficulties to treat highly vitrified and glazed quarry tiles.



#### ATTENTION:

Carefully read the recommendations printed on the label. Always test before use. Do not dispose of the container in the environment after use, follow the disposal information indicated on the label. Keep out of reach of children. The product has anti-stain properties but does not protect surfaces from acids. Check the actual resistance of the material to the product on a hidden portion of the surface to be treated. When using the product, use suitable PPE and consult the safety data sheet.